

BEYER WEAVER & THOMAS, LLP

INTELLECTUAL PROPERTY LAW
2030 Addison Street, Seventh Floor, Berkeley, CA 94704
Telephone: (510) 843-6200 Facsimile: (510) 843-6203
www.beyerlaw.com

FACSIMILE COVER SHEET

January 21, 2004

Receiver: Examiner Elizabeth S. Quan

TEL #:

FAX #: 571-273-1261

Sender: Michael L. Louie

Re: Application Serial No.: 09/835,198

Pages Including Cover Sheet(s): 18

MESSAGE:

Please see attached Amendment B with corrected claim numbering.

CONFIDENTIALITY NOTE

The information contained in this facsimile (FAX) message is legally privileged and confidential information intended only for the use of the receiver or firm named above. If the reader of this message is not the intended receiver, you are hereby notified that any dissemination, distribution or copying of this FAX is strictly prohibited. If you have received this FAX in error, please immediately notify the sender at the telephone number provided above and return the original message to the sender at the address above via the United States Postal Service. Thank you.

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Nichols

Attorney Docket No.: RDYNP007

Application No.: 09/835,198

Examiner: Quan, E.S.

Filed: April 13, 2001

Group: 1743

Title: MASS RATE ATTENUATOR

CERTIFICATE OF TRANSMISSION

I hereby certify that this correspondence is being transmitted via facsimile to the U.S. Patent and Trademark Office, Attention: Examiner Elizabeth S. Quan at facsimile telephone number (571) 273-1261 on January 21, 2004.

Signed: 

Deborah Neill

AMENDMENT B

Commissioner for Patents
Box Fee Amend
Alexandria, Virginia 22313

Dear Sir:

This is an Amendment B in response to the Final Office Action dated September 9, 2003, and for the RCE filed December 8, 2003, for the above-identified patent application.

IN THE SPECIFICATION

Please amend paragraph, starting at page 15, line 25 through page 16, line 4 as follows:

In Fig. 6, the opposite end portions 282, 284 of the aliquot passage lie on concentric circles ~~290~~291, 292 of different diameters, and the rotor turns about an axis 294. With the bypass arrangement of Figs. 6-8, the aliquot passage is very rapidly filled with fluid in its first position. This allows rapid cycling of the rotor or shuttle, at a back and forth rate such